









ENOLA ROUND S
WL, single

100-240V ~50/60Hz | 500mA
Systemleistung: 6W
Material: Aluminium / Glas

ENOLA ROUND M
WL, single

220-240V ~50/60Hz | 500mA
Systemleistung: 11W
Material: Aluminium / Glas

ENOLA ROUND L
WL, single

220-240V ~50/60Hz | 900mA
Systemleistung: 36W
Material: Aluminium / Glas



		A → G
1003422	450/500lm 3000/4000K	A ↑ G ↓ E



■ Abstandshalter Art. Nr. 1002853	
■ Reflektor 60° Art. Nr. 1005262	



		A → G
1003423	860/980lm 3000/4000K	A ↑ G ↓ E



■ Abstandshalter Art. Nr. 1002853	
■ Linse 19° Art. Nr. 1005205	
■ Linse asymmetrisch Art. Nr. 1005206	
■ Reflektor 60° Art. Nr. 1005207	



		A → G
1003440	3300/3700lm 3000/4000K	A ↑ G ↓ E



■ Abstandshalter Art. Nr. 1002853	
■ Reflektor 60° Art. Nr. 1005263	

Variante	Art. Nr.
450/500lm 3000/4000K CRI90	
■ anthrazit	1003422

Variante	Art. Nr.
860/980lm 3000/4000K CRI90	
■ anthrazit	1003423

Variante	Art. Nr.
3300/3700lm 3000/4000K CRI90	
■ anthrazit	1003440