







ENOLA ROUND S  
CL

220-240V ~50/60Hz | 500mA  
Systemleistung: 9W  
Material: Aluminium / Glas

ENOLA ROUND M  
CL

220-240V ~50/60Hz | 500mA  
Systemleistung: 11W  
Material: Aluminium / Glas

ENOLA ROUND L  
CL

220-240V ~50/60Hz | 900mA  
Systemleistung: 36W  
Material: Aluminium / Glas



		A → G
1003426	540/610lm 3000/4000K	A ↑ G ↓ E



■ Abstandshalter  
Art. Nr. 1003479  
■ Reflektor 60°  
Art. Nr. 1005262



		A → G
1003427	840/960lm 3000/4000K	A ↑ G ↓ E



■ Abstandshalter  
Art. Nr. 1003479  
■ Linse 19°  
Art. Nr. 1005205  
■ Linse asymmetrisch  
Art. Nr. 1005206  
■ Reflektor 60°  
Art. Nr. 1005207



		A → G
1003442	3200/3500lm 3000/4000K	A ↑ G ↓ E



■ Abstandshalter  
Art. Nr. 1003479  
■ Reflektor 60°  
Art. Nr. 1005263



Variante	Art. Nr.
540/610lm   3000/4000K   CRI90	
■ anthrazit	1003426

Variante	Art. Nr.
840/960lm   3000/4000K   CRI90	
■ anthrazit	1003427

Variante	Art. Nr.
3200/3500lm   3000/4000K   CRI90	
■ anthrazit	1003442